



# SAFETY DATA SHEET

[In accordance with the criteria of Regulation No 1907/2006 (REACH) as amended]

## Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name: SULPHURIC ACID (VI)  
 Chemical name: sulphuric acid (VI) >51%  
 Index number: 016-020-00-8  
 Registration number: 01-2119458838-20-0110

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses:

Production of sulphuric acid.  
 Use of sulphuric acid as an intermediate in manufacture of inorganic and organic chemicals incl. fertilizers.  
 Use of sulphuric acid as a processing aid, catalyst, dehydrating agent, pH regulator.  
 Use of sulphuric acid for extractions and processing of minerals, ores.  
 Use of sulphuric acid in the process of surface treatments, purification and etching.  
 Use of sulphuric acid in electrolytic processes.  
 Use of sulphuric acid in gas purification, scrubbing, flue gas scrubbing.  
 Use of sulphuric acid in production of sulphuric acid contained batteries.  
 Use of sulphuric acid in maintenance of sulphuric acid contained batteries.  
 Use of sulphuric acid in recycling of sulphuric acid contained batteries.  
 Use of sulphuric acid contained batteries.  
 Use of sulphuric acid as laboratory chemicals.  
 Use of sulphuric acid in industrial cleaning.  
 mixing, preparation and repackaging of sulphuric acid.  
 For professional applications as a cleaning agent.

Uses advised against: not determined.

### 1.3. Details of the supplier of the safety data sheet

Manufacturer: Zakłady Górniczo-Hutnicze „Bolesław” Spółka Akcyjna  
 Address: ul. Kolejowa 37, 32-332 Bukowno, Poland  
 Telephone/Fax number: +48 32 295 51 00/+48 32 295 50 00  
 E-mail address for a competent person responsible for sds: biuro@thetaconsulting.pl

### 1.4. Emergency telephone number

112, Factory dispatcher: +48 32 296 55 80 (on call 24h)

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

Skin Corr. 1A H314, Eye Dam. 1 H318  
 Causes severe skin burns and eye damage. Causes serious eye damage.

### 2.2. Label elements

#### Hazard symbols and signal words



DANGER

#### Hazard statements

H314 Causes severe skin burns and eye damage.



# SAFETY DATA SHEET

## Precautionary statements

P102	Keep out of reach of children.
P223	Do not allow contact with water.
P260	Do not breathe vapours/ spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P405	Store locked up.
P501	Dispose of contents/container to properly labelled waste containers according to national law.

## 2.3. Other hazards

Substance does not meet the PBT or vPvB criteria in accordance with the Annex XIII of the REACH Regulation. The substance has not been included in the list established in accordance with Article 59 (1) for having endocrine disrupting properties, or as substance identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 (3) or Commission Regulation (EU) 2018/605.

## Section 3: Composition/information on ingredients

### 3.1. Substances

Chemical name:	sulphuric acid (VI) > 51 %
Synonyms:	sulphuric acid concentrated (VI), sulphuric acid contact, sulphuric acid technical concentrated, sulphuric acid containing above 51 % of acid
Range:	100 %
Index number:	016-020-00-8
CAS number:	7664-93-9
EC number:	231-639-5
Specific concentration limits:	Eye Irrit. 2 H319 5 % ≤ C < 15 % Skin Corr. 1A H314 C ≥ 15 % Skin Irrit. 2 H315 5 % ≤ C < 15 %

Substance for which Union workplace exposure limits have been assigned.

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** immediately take off contaminated clothes. Wash out skin with plenty of cool water. Do not use soaps or alkaline neutralizing agents. Use aseptic dressing, immediately call a doctor.

**Eye contact:** immediately wash out with plenty of water with the eyelid hold wide open, for at least 10-15 min. Avoid powerful water stream – risk of cornea damage. Remove any contact lenses. Use aseptic dressing. Obtain medical attention immediately.

**Ingestion:** do not cause vomiting. Rinse mouth with water, then drink plenty of water. Do not give anything to drink to unconscious. Do not give agents to neutralize acids. Immediately call a doctor, show him label.

**Inhalation of vapours:** remove to fresh air, keep warm and calm. Consult a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

**Eye contact:** causes severe eyelid and eyeball burns and eye damage, redness, burning sensation, pain; can cause sight lost or permanent cornea opacity.

**Skin contact:** chemical burns, redness, burning sensation, pain and thermal burns (exothermic reaction with moisten skin).

**Inhalation of vapours:** tearing, conjunctiva and cornea burns, throat pain, cough, shortness of breath, glottis cramp, larynx edema, bronchia cramp, lungs edema, painful burns of respiratory tract.



# SAFETY DATA SHEET

Ingestion: cause burns of oral cavity, throat, esophagus, stomach, thirst sensation, nausea, vomiting, diarrhea, alimentary canal hemorrhage, impact.

4.3. Indication of any immediate medical attention and special treatment needed

Physician makes a decision regarding further medical treatment after thoroughly examination of the injured.  
Symptomatic treatment.

## Section 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: substance is not flammable. Use extinguishing measures that are appropriate to the environment. Recommended extinguishing media: dry extinguishing type A,B,C.

Unsuitable extinguishing media: water. Do not let water to get into the container with acid.

5.2. Special hazards arising from the substance or mixture

May produce toxic and corrosive fumes of sulphur and carbon oxides if burning. Do not inhale combustion products – it can be dangerous for health.

5.3. Advice for firefighters

Personal protection typical in case of fire. Do not stay in the fire zone without self-contained breathing apparatus and protective clothing resistant to chemicals Remove containers exposed to high temperatures from the risk area. Collect used extinguishing media.

## Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Limit the access for the outsiders into the breakdown area, until the suitable cleaning operations are completed. In case of release of large amounts of the substance, it is necessary to take appropriate steps to prevent it from spreading into the environment. Ensure that the effects of the accident was removed only by trained personnel. Wear adequate personal protective equipment. Avoid direct contact with the product. Do not breathe vapours, ensure adequate ventilation.

6.2. Environmental precautions

In case of release of large amounts of the substance, it is necessary to take appropriate steps to prevent it from spreading into the environment. Do not let the substance to get through the surface or ground water, soil, sewage system, wells, basements etc. Notify relevant emergency services.

6.3. Methods and material for containment and cleaning up

Large spillage embank and pump out to emergency containers. Small spillage cover up with material absorbing liquids, e.g. sand, soil and acid-neutralizing agents, e.g. calcium or sodium carbonate, ground limestone, dolomite. Pick it up to labeled waste container. To remove sulphuric acid spillages do not use flammable materials, e.g. sawdust. Rinse the contaminated area thoroughly with water and ventilate well.

6.4. Reference to other sections

Appropriate conduct with waste product – section 13. Appropriate personal protective equipment – section 8.

## Section 7: Handling and storage

7.1. Precautions for safe handling

Handle in accordance with good occupational hygiene and safety practices. Ensure adequate ventilation. Before break and after work wash hands carefully. Avoid contact with eyes and skin. Do not form and inhale vapours and aerosol. Not used containers keep tightly closed. Do not let the substance to get to the mouth. Never add water to acid. When diluting, add slowly acid to water and mix carefully. Do not use sparkling equipment for opening vessels (possibility to create explosive gas-hydrogen, inside). Hygroscopic substance, avoid contact with water.

7.2. Conditions for safe storage, including any incompatibilities

Keep only in original, tightly closed, correctly labeled containers, in cool, dry and well-ventilated place. Floor in warehouse should be made of acid-proof materials. Avoid direct expose to sunlight.



# SAFETY DATA SHEET

Protect against fire sources and heat. Protect from water and moisture. Keep away from food, beverages or feed for animals. Do not store near bases. Recommended materials for containers and fixtures:

- steel – only to contact with concentrated acid (92-98%)
- acid-proof steel
- Teflon®
- polyethylene (in 20°C resistance in every concentration)
- polypropylene (in 20°C resistance in every concentration)

### 7.3. Specific end use(s)

No information about the applications other than those specified in subsection 1.2.

Details relating to specific applications are provided in the exposure scenarios, annexed to the SDS.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

Occupational exposure limit value in European Community:

Substance	Limit value			Note
	8-hours	Short-term		
Sulphuric acid (mist) [CAS 7664-93-9]	0,05 mg/m <sup>3</sup>	-	-	(1)(2)

<sup>(1)</sup> When selecting an appropriate exposure monitoring method, account should be taken of potential limitations and interferences that may arise in the presence of other sulphur compounds.

<sup>(2)</sup> The mist is defined as the thoracic fraction

Legal Basis: Commission Directive 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, 2019/1831/EU.

Please check also any national occupational exposure limit values in your country.

#### Recommended control procedures

Procedures concerning the control over the dangerous components concentrations in the air and control over the air quality in the workplace – if they are available and justified for the position – in accordance with the European Standards, with the conditions within the exposure place and a proper test methodology adapted to the working conditions.

#### DNEL values

Route	Exposure pattern	DNEL (workers)
Inhalation	Acute - local effects	0.1 mg/m <sup>3</sup> (exposure 15 min.)
		0.05 mg/m <sup>3</sup> (exposure 8h)
	Long-term - systemic effects	0.1 mg/m <sup>3</sup> (exposure 15 min.)
		0.05 mg/m <sup>3</sup> (exposure 8h)

The extensive toxicity database for sulphuric acid demonstrates an absence of systemic toxicity. Effects seen in all studies are local (site of contact) and are attributable to the corrosive nature of the substance. The substance will dissociate under physiological conditions to form hydrogen and sulphate ions, both of which are naturally present. Exposure must be eliminated or minimized through the use of engineering controls and PPE.

#### PNEC values

PNEC	Assessment factor	Value
freshwater	10	0.0025 mg/l
marine water	—	0.00025 mg/l
sewage treatment plant	10	8.8 mg/l
sediment, freshwater	—	0.002 mg/kg d.w.
sediment, marine water	—	0.002 mg/kg d.w.



# SAFETY DATA SHEET

## 8.2. Exposure controls

### Appropriate engineering controls

Use the product in accordance with good occupational hygiene and safety practices. Do not eat, drink and smoke during the work. Before break and after work carefully wash hands. Avoid skin and eyes contamination. Do not create and inhale vapours. In the workplace Ensure adequate generally ventilation and/or locally in order to keep the concentration of noxious agent in the air below the determined permissible limits. Local exhaust ventilation is preferred because it removes impurities from the place of their formation, not allowing their spread. If during work processes there is a risk of splashing the workers with caustic agents - safety showers and separate eyewash stations should be installed in horizontal line from the posts on which the processes are carried out.

### Individual protection measures, such as personal protective equipment

The necessity to use and selection of appropriate personal protective equipment should take into account the type of risk posed by the product, working conditions and the way of handling the product. The personal protective equipment used must meet the requirements of Regulation (EU) 2016/425 and the relevant standards. The employer is obliged to provide protection measures appropriate to the activities performed and meeting all quality requirements, including their maintenance and cleaning. Any contaminated or damaged PPE must be replaced immediately.

### Hand protection

Wear the protective gloves, acid-proof (EN 374). In the case of short-term contact use protective gloves on the level of effectiveness of 2 or higher (breakthrough time > 30 min.). In the case of long term contact use protective gloves on the level of effectiveness 6 (breakthrough time > 480 min.).

The material that the gloves are made of must be impenetrable and resistant to the product's effects. The selection of material must be performed with consideration of breakthrough time, penetration speed and degradation. Moreover, the selection of proper gloves depends not only on the material, but also on other quality features and changes depending on the manufacturer. The producer should provide detailed information regarding the exact breakthrough time. This information should be followed.

### Body protection

Wear acid-proof protective clothes and shoes.

### Eye/face protection

Wear protective glasses according to EN 166.

### Respiratory protection

In case of exceeding the highest permissible concentration values, in emergency situations it is advised to use AX type absorption equipment (class 1/protection against gases of volume concentration in air the below 0,1 %; class 2/ protection against gases of concentration in the air below 0,5 %; class 3/ protection against gases of volume concentration in the air up to 1 %). If the oxygen concentration is  $\leq 19\%$  and/or max gas concentration in the air is  $\geq 1,0\%$  of total volume, self-contained breathing apparatus must be used.

### Thermal hazards

Do not occur.

### Environmental exposure controls

Do not allow the substance to contaminate surface water/ground water. Any emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	oily liquid
Colour:	colorless to yellow
Odour:	sharp, pungent
Melting point/freezing point:	-1.11÷-3.0 °C (acid 98 %)
Boiling point or initial boiling point and boiling range:	ca. 310 °C (acid 98 %)



# SAFETY DATA SHEET

Flammability:	not applicable
Lower and upper explosion limit:	not determined
Flash point:	not applicable, the product is not flammable
Auto-ignition temperature:	not applicable, the product is not self-igniting
Decomposition temperature:	338 °C
pH:	< 1 (49 g/l, 25 °C)
Kinematic viscosity:	not determined
Solubility:	soluble in water, in ethanol
Partition coefficient n-octanol/water (log value):	not determined
Vapour pressure:	< 0.001 hPa (20 °C, acid 96 %) 1.3 hPa (145.8 °C) 2.8 hPa (180 °C)
Density and/or relative density:	1.835 g/cm <sup>3</sup> (20 °C, acid 93-100 %)
Relative vapour density:	not determined
Particle characteristics:	not applicable
9.2. Other information	
Crystallization temperature:	10.4 °C (acid 98,3 %)
Dynamic viscosity:	22.5 mPa·s (20 °C)

## Section 10: Stability and reactivity

- 10.1. Reactivity  
Highly reactive substance.
- 10.2. Chemical stability  
The product is stable under normal conditions.
- 10.3. Possibility of hazardous reactions  
In case of contact with metals hydrogen is formed, extremely flammable gas, with explosive properties. Sulphuric acid concentrated reacts with organic compounds and can cause ignition of powdery organic materials. Reactions with water and bases are rapid and strongly exothermic.
- 10.4. Conditions to avoid  
Water, moisture, excessive heating above 150 °C.
- 10.5. Incompatible materials  
Alkaline metals, rare earth metals, basics, ammonia, phosphorus, phosphorus oxides, hydrides, permanganates, nitrates, nitrites, acetylene, chlorates, nitrates, carbides, peroxides, picrides, organic solvents, nitro compounds, aniline, oxyhalogen compounds, metals and alloys, flammable materials, compounds kind halogen-halogen.
- 10.6. Hazardous decomposition products  
Not known.

## Section 11: Toxicological information

- 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

### Acute toxicity

LD <sub>50</sub> (rat, oral)	2140 mg/kg
LC <sub>50</sub> (rat, inhalation)	347 ppm/1h
LC <sub>50</sub> (mouse, inhalation)	0.85 mg/l/4h
LC <sub>50</sub> (mouse, inhalation)	0.6 mg/l/8h
LC <sub>50</sub> (rabbit, inhalation)	1.47 mg/l/3.5h
LC <sub>50</sub> (guinea pig, inhalation)	18 mg/m <sup>3</sup> /8h



# SAFETY DATA SHEET

Based on available data, the classification criteria are not met.

## Skin corrosion/irritation

Substance causes severe burns in skin contact.

## Serious eye damage/irritation

Substance causes severe eye damage.

## Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

## Germ cell mutagenicity

NOAEC (inhalation) 19.3 mg/m<sup>3</sup>

Negative in tests.

## Carcinogenicity

Negative in tests. In spite of conduct many epidemiological tests, so far is not improved direct connection between exposure to sulphuric acid mists and laryngeal cancer. Individual studies are imprecise and do not adequately take into account confounding factors such as smoking and exposure to other occupational chemicals.

## Reproductive toxicity

Negative in tests.

## STOT-single exposure

Based on available data, the classification criteria are not met.

## STOT-repeated exposure

Exposure repeated, target organ: larynx

NOAEC (inhalation) 0.3 mg/m<sup>3</sup>

Based on available data, the classification criteria are not met.

## Aspiration hazard

Based on available data, the classification criteria are not met.

## Information on likely routes of exposure

Routes of exposure: eye contact, skin contact, inhalation, ingestion. For more information on the impact of each possible route of exposure, see subsection 4.2.

## Symptoms related to the physical, chemical and toxicological characteristics

See subsection 4.2.

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

See subsection 4.2.

## 11.2 Information on other hazards

### Endocrine disrupting properties

The substance has not been included in the list established in accordance with Article 59 (1) for having endocrine disrupting properties, or as substance identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 (3) or Commission Regulation (EU) 2018/605.

### Other information

Not known.

## Section 12: Ecological information

### 12.1. Toxicity

LC <sub>50</sub> (fish)	16-28 mg/l/96h/ <i>Lepomis macrochirus</i>
LC <sub>10</sub> /EC <sub>10</sub> or NOEC (fish)	0.025 mg/l
EC <sub>50</sub> (invertebrates)	> 100 mg/l/48h/ <i>Daphnia magna</i>
LC <sub>10</sub> /EC <sub>10</sub> or NOEC (invertebrates)	0.15 mg/l
EC <sub>50</sub> (algae)	> 100 mg/l/72h/ <i>Desmodesmus subspicatus</i>
LC <sub>10</sub> /EC <sub>10</sub> or NOEC (algae)	100 mg/l



# SAFETY DATA SHEET

Substance is not classified as hazardous for the environment.

## 12.2. Persistence and degradability

Undergoes the biological degradation.

## 12.3. Bioaccumulative potential

Bioaccumulation not expected.

## 12.4. Mobility in soil

Product can penetrate a soil; soluble in water, spread in aquatic environment.

## 12.5. Results of PBT and vPvB assessment

Substance does not meet the PBT or vPvB criteria.

## 12.6. Endocrine disrupting properties

The substance has not been included in the list established in accordance with Article 59 (1) for having endocrine disrupting properties, or as substance identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 (3) or Commission Regulation (EU) 2018/605.

## 12.7. Other adverse effects

The mixture is not classified as hazardous to the ozone layer. The possibility of other harmful effects of individual components of the mixture on the environment should be considered (e.g. global warming potential).

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

Disposal methods for the product: disposal in accordance with the local legislation. Do not remove with household garbage. Waste product store in original containers. Consider recycling. Dispose via licensed waste disposal contractor. Sulphuric acid neutralize with 10% milk of lime.

Disposal methods for used packing: reuse/recycling/liquidation of empty containers dispose in accordance with the local legislation. Reuse tanks after commercial cleaning. Disposable containers transfer to waste contractor.

Legal basis: Directive 2008/98/EC as amended, 94/62/EC as amended.

## Section 14: Transport information

### 14.1. UN number or ID number

UN 1830

### 14.2. UN proper shipping name

SULPHURIC ACID with more than 51% acid

### 14.3. Transport hazard class(es)

8

### 14.4. Packing group

II

### 14.5. Environmental hazards

Not classified as hazardous for the environment.

### 14.6. Special precautions for user

Use appropriate personal protective equipment according to section 8.

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable.





# SAFETY DATA SHEET

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

ADR Agreement Concerning the International Carriage of Dangerous Goods by Road.

IMDG Code International Maritime Dangerous Goods Code.

IATA The International Air Transport Association regulations.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC as amended.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 as amended.

Commission Regulation (EU) No 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH).

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste and repealing certain Directives as amended.

European Parliament and Council Directive 94/62/EC of 20 December 1994 on packaging and packaging waste as amended.

Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC.

Commission Directive 2000/39/EC of 8 June 2000 establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Commission Directive 2006/15/EC of 7 February 2006 establishing a second list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC.

Commission Directive 2009/161/EU of 17 December 2009 establishing a third list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Commission Directive 2000/39/EC.

Commission Directive 2017/164/EU of 31 January 2017 establishing a fourth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC, and amending Commission Directives 91/322/EEC, 2000/39/EC and 2009/161/EU.

Commission Directive 2019/1831/EU of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC.

### 15.2. Chemical safety assessment

Chemical Safety Report has been prepared for identified use of substance.

## Section 16: Other information

### Full text of indicated H phrases mentioned in section 3

H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.

### Clarification of aberrations and acronyms

Skin Corr. 1A	Skin corrosion category 1A
Eye Irrit. 2	Serious eye damage/eye irritation, category 2
Skin Irrit. 2	Skin corrosion/irritation, category 2
Eye Dam. 1	Serious eye damage category 1
PNEC	Predicted no effect concentration
DNEL	Derived no-effect level
NOAEC	No Observed Adverse Effect Concentration
NOEC	No Observed Effect Concentration
PBT	Persistent, Bioaccumulative and Toxic substance
vPvB	very Persistent, very Bioaccumulative substance



## SAFETY DATA SHEET

### Trainings

Before commencing working with the product, the user should learn the Health & Safety regulations, regarding handling chemicals, and in particular, undergo a proper workplace training.

People associated with transport of hazardous materials in accordance with ADR should be adequately trained for their job responsibilities (general training, bench and safety).

### Key literature references and sources of data

This SDS was prepared on the basis of on manufacturer's data, literature data, online databases, our knowledge and experience, taking into account the current legislation.

### Additional information

Date of update: 30.09.2022

Version: 6.0/EN

Safety Data Sheet made by: THETA Consulting Sp. z o.o. (based on producer's data)

The information above is based on a current available data concerning the product, but also on the experience and knowledge in this field of the producer. They are neither a quality description of the product nor a guarantee of particular features. They are to be treated as aid to safety in transport, storage and usage of the product. That does not free the user from the responsibility of improper usage of the information above and also of improper compliance with the law norms in the field.